

**IF5M110ZM05-1**

<b>Weight (Gross with Carton)</b>	<b>Gr</b>	240
<b>Operational Frequency</b>		50 Hz
<b>Operational Voltage</b>		110V AC
<b>Product</b>		LED Beacon 55mm
<b>Control</b>		Key Control
<b>Mounting</b>		M22 Screw
<b>Color</b>		Multicolor
<b>Illumination</b>		Constant
<b>Cable</b>		1mt Cable
<b>Volume</b>		90 dB
<b>Power Consumption</b>		11VA
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	1 Hz
<b>Insulation Voltage</b>	<b>Ui</b>	300V
<b>Operating Temperature</b>		-25 °C /+70 °C
<b>Protection Degree</b>		IP65
<b>Cable Section</b>		Cable 0,50 mm <sup>2</sup>
<b>Production Time</b>		31.12.1899 00:00:00
<b>Serial</b>		IF Series
<b>Buzzer</b>		With Buzzer
<b>Electrical Life</b>	<b>Min Hour</b>	10000
<b>Specifications</b>	Heat resistant, clear vision Polycarbonate signal module	
	Monoblock construction	
	Easy wiring	
	Easy to install to 22mm hole	