



## L2K13MIM211

|                                       |             |                              |
|---------------------------------------|-------------|------------------------------|
| Product                               |             | Limit Switch                 |
| Contact                               |             | 1NO+1NC                      |
| Actuator                              |             | Roller Lever                 |
| Actuator Dia                          |             | 22 mm                        |
| Current                               | Ie          | 3 A (240V AC)                |
| Usage Category                        |             | AC15                         |
| Mechanical Life                       | Min Qty     | 10000000                     |
| Electrical Life                       | Min Qty     | 1000000                      |
| Operating Frequency                   | On-Off/Hour | Mech. 3000 Elec. 1800        |
| Insulation Voltage                    | Ui          | 300 V                        |
| Impulse Withstand Voltage             | Uimp        | 2.5 kV                       |
| Dielectric Strength (Body-Contact)    |             | 1.890V AC                    |
| Dielectric Strength (Contact-Contact) |             | 1.890V AC                    |
| Isolation Resistance                  |             | 10 MΩ (500 V DC)             |
| Operating Temperature                 |             | -25 / + 80 °C                |
| Pollution Degree                      |             | 3                            |
| Protection Degree                     |             | IP65                         |
| Contact Material                      |             | AgNi                         |
| Cable Section                         |             | 1-2.5 mm <sup>2</sup>        |
| Screw Torque                          |             | 1.5Nm                        |
| Short Circuit Breaking Capacity       | Ics         | 1 kA                         |
| Production Time                       |             | 31.12.1899 00:00:00          |
| Serial                                |             | L2 Metal Body                |
| Contact Action                        |             | Snap Action                  |
| Actuator Material                     |             | Metal                        |
| Specifications                        |             | Metal Body and Plastic Cover |
|                                       |             | 3 side PG13,5 holes          |

Various actuator options with wide sensitive contact block alternatives for all kind of applications

**Standards / Certificates** TS EN 60947-5-1 UL 508 VDE 0660

