


**MBSP012B**

|                              |                 |                                       |
|------------------------------|-----------------|---------------------------------------|
| <b>Bulb Type</b>             |                 | Led                                   |
| <b>Operating Current</b>     |                 | 18 mA                                 |
| <b>Operational Frequency</b> |                 | 50 Hz                                 |
| <b>Operational Voltage</b>   |                 | 12V AC/DC                             |
| <b>Product</b>               |                 | Pilot                                 |
| <b>Color</b>                 |                 | White                                 |
| <b>Illumination</b>          |                 | with LED                              |
| <b>Dia</b>                   |                 | 22 mm                                 |
| <b>Power Consumption</b>     |                 | 0.3 W                                 |
| <b>Insulation Voltage</b>    | <b>Ui</b>       | 250 V                                 |
| <b>Operating Temperature</b> |                 | -15 / + 70 °C                         |
| <b>Protection Degree</b>     |                 | IP50                                  |
| <b>Cable Section</b>         |                 | 1.5-2.5 mm <sup>2</sup>               |
| <b>Screw Torque</b>          |                 | 1,5 Nm                                |
| <b>Production Time</b>       |                 | 31.12.1899 00:00:00                   |
| <b>Serial</b>                |                 | MB Series Plastic                     |
| <b>Electrical Life</b>       | <b>Min Hour</b> | 10000                                 |
| <b>Specifications</b>        |                 | Non-flammable V0 PA6.6 contact blocks |
|                              |                 | Monoblock strong body                 |
|                              |                 | Finger safe protection                |